

**Hygro-Thermometer Humidity Alerts w/Dew Point**  
Programmable Alarms warn of High or Low Humidity Conditions

**Features:**

- Large, easy-to-read triple LCD displays % Relative Humidity, Temperature and Dew Point
- %RH audible and visual alarms, with adjustable set points, alert when humidity exceeds set limit
- Probe clips onto meter or extends on 18" (457mm) cable (Model 445815 only)
- Max/Min with Reset function
- Rear calibration adjustment pot for Humidity and Temperature (Model 445815 available with NIST certification and optional Calibration Standards)
- Humidity: 10 to 99%
- Temperature: 14 to 140°F (-10 to 60°C)
- Basic Accuracy: ±4%RH; ±1.8°F/1°C
- Dimensions 4.3x3.9x0.78" (109x99x20mm)  
Weight: 6oz (169g)
- Complete with built-in stand, wall mount bracket, remote sensor (Model 445815) and 2 AAA batteries; Optional calibration salt bottles for Model 445815



**Applications**

- In summertime, identifies and warns when conditions for mold growth exist
- In wintertime, identifies and warns when low humidity conditions for static electricity exist
- Remote probe (Model 445815) allows for measurements behind walls or in difficult to access locations
- Air temperature and dew point temperature indicate where condensation may occur
- Monitor conditions in laboratories, storage areas and other controlled environment settings
- Ideal solution when traceable ISO calibrations are required by operating standards (Model 445815 only)



**Ordering Information:**

<b>445814</b> .....	Humidity Alert Hygro-Thermometer with Dew Point .....	<b>\$39.99</b>
<b>445815</b> .....	Humidity Alert II Hygro-Thermometer with Dew Point .....	<b>\$49.99</b>
<b>445815-NIST</b> ..	Humidity Alert II Hygro-Thermometer w/DP w/NIST certificate ..	<b>\$174.99</b>
<b>445580-C</b> .....	Optional 33% and 75 % RH calibration standards .....	<b>\$45.99</b>



**"Make mine an Extech!"™**  
[www.extech.com](http://www.extech.com)