

Waterproof ExStik® II Dissolved Oxygen Kit

Easy to replace screw on membrane cap with extension cable and weighted probe guard

Features:

- Convenient kit adds versatility on measuring Dissolved Oxygen in laboratories or out in the field with a 16ft (5m) extension cable and probe weight guard for taking easy measurements in tanks or streams
- Oxygen level displayed as % Saturation from 0 to 200.0% or Concentration from 0 to 20.00ppm (mg/L)
- Adjustable Altitude Compensation (0 to 20,000ft in 1,000ft increments)
- Adjustable Salinity Compensation from 0 to 50ppt
- Analog bargraph indicates trends
- Memory stores up to 25 data sets with DO and Temperature reading
- Self calibration on power up
- Data Hold, Auto power off, Low battery indicator
- Waterproof to IP57
- Complete with ExStik II DO meter, DO electrode, protective sensor cap, DO603 replacement membrane Kit, 16ft (5m) extension cable, weighted probe guard, four 3V CR-2032 batteries, 48" (1.2m) neckstrap, and hard carrying case



DO603 Membrane Kit includes 6 screw on membrane caps, 15mL filling solution and polishing paper



Weighted probe guard




16ft (5m) extension cable attached to meter



Bonded membrane cap for easy replacement



Sample testing with extension cable attached to meter



Sample testing with the meter in a laboratory environment

Specifications:	Range	Max Resolution	Basic Accuracy
DO (saturation mode)	0 to 200.0%	0.1%	±2% FS
DO (concentration mode)	0 to 20.00ppm (mg/L)	0.01ppm (mg/L)	±0.4ppm (mg/L)
Temperature:	32 to 122°F (0 to 50°C)	0.1°F/°C	±1.8°F (1°C)
Meter Dimensions	1.4x 6.9x1.6" (36 x176 x 41mm)		
Meter Weight:	3.8oz (110g)		

Ordering Information:

DO600-KExStik® II Dissolved Oxygen Kit